Prolong the life of your tools

Available in freestanding & drawbar configurations



DryAR

The Solution to Your Portable Compressor Moisture Problems

DryAIR works by effectively removing harmful moisture from the discharge air of portable gas & diesel compressors. Cools air to within 15° of ambient temperature.

DryAIR units deliver cleaner compressed air, resulting in virtually no contamination on blast surfaces. Primer and paint adhere better, without *fish-eye* and troublesome spotting on finish coats.

Moisture is a poor lubricant and causes premature failure of paving breakers, jackhammers, rivet busters and related air tools. DryAIR will make a significant difference in prolonging the life of your tools.







DryAIR 250TMA

Tongue-Mount units are easy to install and make a valuable addition to Doosan / IR portable compressors. They can easily be retrofitted to mount on various other brands as well.

PERFORMANCE

MAXIMUM FLOW 250 CFM

MAXIMUM OPERATING PRESSURE

200 psig

MAXIMUM PRESSURE DROP

5 psig

FAN POWER REQUIREMENT

17.5 amps, 12 volts DC

DIMENSIONS

30" W x 14" D x 30" H

WEIGHT

50 lbs

DryAIR 250FSA CLASSIC

Free-Standing self-contained units are mounted in a rugged box frame designed to withstand the rigorous demands of the construction industry. They can be used on any gas or diesel portable compressor.

PERFORMANCE

MAXIMUM FLOW

250 CFM

MAXIMUM OPERATING PRESSURE

200 psig

MAXIMUM PRESSURE DROP

5 psig

FAN POWER REQUIREMENT

17.5 amps, 12 volts DC

DIMENSIONS

24" W x 19" D x 32" H

WEIGHT

70 lbs

DryAIR 400FS/TM

Convertable **Freestanding** or **Tongue-Mount** aftercoolers designed for mid-sized Doosan / IR portable diesel compressors. They can easily be retrofitted to mount on various other brands as well.

PERFORMANCE

MAXIMUM FLOW

400 CFM

MAXIMUM OPERATING PRESSURE

200 psig

MAXIMUM PRESSURE DROP

5 psig

FAN POWER REQUIREMENT

9.6 amps, 24 volts DC

DIMENSIONS

48" W x 24" D x 30" H

WEIGHT

170 lbs